# **Internal Bond Tester**



# **Usage**

For the determination of internal bonding force of paper.

# **Applicable standards**

TAPPI T 569, TAPPI T 833

# **Device description**

This device comes with a built-in digital display and is microprocessor controlled. The standard configuration is delivered with a medium range pendulum. All the parts are built into a sturdy steel frame. A pendulum mechanism pulls the pendulum back to starting position if the test is carried out. Push down sample holder for quick changing of the base plate with the sample and the aluminum angle.

# **Test description**

The sample that needs testing is placed in the measuring area. By pushing the start button the pendulum is released and hits the aluminum angle, glued on the sample with double adhesive tape. The sample is pushed away and the needed energy is measured and displayed in J/m².

# **Specification**

- Digital display, microprocessor controlled
- Automatic pendulum return to starting position
- Easy inserting of the sample base with quick changing mechanism
- Delaminating angle of the pendulum to the surface of the sample: 90°
- Easy insertion of the sample base with quick changing mechanism
- 5 support base and 5 aluminum angles as standard delivery
- Display of values selectable in J/m², kg/cm, ft.lb/in²
- RS232 Port

#### **Connections**

Electricity: 110 - 230 V, 50 - 60 Hz AC

Air: 600 kPa



Karl Schröder KG Mierendorffstrasse 28 D-69469 Weinheim

Web: www.schroeder-prueftechnik.de @: info@schroeder-prueftechnik.de

T: +49 6201 9068-0 F: +49 6201 9068-29



Automatic sample preparation (left). Manual sample preparation (right).

# **Models**

Article code	Device	
RL-IBT-A4	Device with manual sample preparation	
	station	
RL-IBT-A2	Device with automatic sample	
	preparation station	

# **Delivery content**

- Instrument with sample preparation station
- 5 base plates
- 5 aluminum angles 1
- double adhesive tape
- Standard delivery with medium range pendulum
  (1.050 J/ m2). More optional pendulums: see below
- Connection cable
- User manual

# **Optional**

- Low weight pendulum with range of 525 J/m²
- High range pendulum with 2.100 J/m<sup>2</sup>
- Double adhesive tapes
- Set aluminum angles (set = 5 pcs)
- Set base plates (set = 5 pcs)

# **Dimensions**

	Net	Gross	
Instrument			
Width	600	750	
Depth	300	450	
Height [mm]	550	700	
Weight [kg]	20	32	
Sample Preparation station			
Width	380	500	
Depth	400	500	
Height [mm]	350	550	
Weight [kg]	30	45	



Karl Schröder KG Mierendorffstrasse 28 D-69469 Weinheim Web: www.schroeder-prueftechnik.de @: info@schroeder-prueftechnik.de

T: +49 6201 9068-0 F: +49 6201 9068-29